

SPECIFICATIONS

MAXIMA

3W: SC900 4W:SC940

Weight capacity:	500 lbs.
Maximum speed ¹ :	Up to 5.25 mph
Ground clearance ³ :	3W: 4.25" 4W: 3.25"
Turning radius ³ :	3W: 50.38" 4W: 54"
Overall length ³ :	3W: 46" 4W: 46.9"
Overall width ³ :	3W: 25.5" 4W: 25.5"
Seat-to-ground height:	22.5"-24.5"
Seat-to-deck height:	3W: 22.3"-22.6" 4W: 24.3"-24.6"
Front tires:	3" x 10" solid
Rear tires:	4" x 10" solid
Suspension:	3W: Rear 4W: Front and rear
Range per charge ^{1,2} :	3W: Up to 18 miles, U-1 (Power Elevating Seat) up to 9.6 miles 4W: Up to 16 miles
Total weight without batteries ^{3,7} :	3W: 171 lbs. 4W: 176 lbs.
Heaviest piece when disassembled ³ :	76 lbs. (rear section)
Standard seating:	Type: Deluxe Contoured medium-back Weight: 40 lbs. ³ Material: Black Vinyl Dimensions: 22" x 18"
Drive system:	Rear-wheel drive, sealed transaxle with 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements ^{3,4,5} :	38 lbs. each (NF 22), 24.5 lbs. each (U-1)
Battery charger:	5-amp, off-board

Color:



Candy Apple Red



Viper Blue



930 E. Main • Farmington, NM
(505) 327-4041

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.

² Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

⁴ AGM or gel cell type required.

⁵ Battery weight may vary based on battery manufacturer.

⁶ U-1 batteries required with power elevating seat.

⁷ Includes standard seat weight.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

FEATURES

- 500 lb. weight capacity
- Black, flat-free, non-marking tires
- Standard front basket
- Ultra heavy-duty drivetrain with 110 amp controller
- Maximum speed up to 5.25 mph
- Redesigned seat for improved comfort
- Easily adjustable tiller
- Durable and stylish rear polyurethane bumper
- Easily accessible tie down points (for transport of unoccupied scooter)
- User-friendly console

OPTIONS

- Power elevating seat (3-wheel only)
- Forearm crutch holder
- Cane/crutch holder
- Wishbone crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag
- Quad cane holder
- Lap belt
- Touch-up paint
- Rearview mirror

Pride® Lifts & Ramps

Compatible Lifts:

- Outlander
- Olympian AutoLift
- Commander 400
- Backpacker®



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®