



3 & 4-WHEEL SCOOTER

FEATURES, PERFORMANCE, AND TRAVEL READY

The **Go-Go® Sport** delivers high-performance and convenience on-the-go. With a 325 lb. weight capacity, charger port in the tiller, and standard front LED lighting and a maximum speed up to 4.7 mph., the Go-Go Sport is feature rich and travel ready.



Go-Go® Sport 4-wheel



Go-Go® Sport 3-wheel



Wraparound Delta Tiller



facebook.com/PrideMobilityProductsCorp



youtube.com/PrideMobility

PRIDE® **MOBILITY** SCOOTERS
LIVE YOUR BEST®

SPECIFICATIONS

GO-GO® SPORT 3W: SC73 (K0801) 4W:SC74

| | |
|---|---|
| Weight capacity: | 325 lbs. |
| Maximum speed ¹ : | Up to 4.7 mph |
| Ground clearance ² : | 3" at frame, 1.5" at motor |
| Turning radius: | 3W: 36" 4W: 50.5" |
| Overall length ² : | 3W: 42" 4W: 43" |
| Overall width ² : | 21.25" |
| Front tires: | 3W: 3" x 8" solid 4W: 3" x 9" solid |
| Rear tires: | 3" x 9" solid |
| Range per charge ^{1,4} : | 3W: Up to 12.7 miles 4W: Up to 12 miles |
| Total weight without batteries ⁵ : | 3W: 92.8 lbs. 4W: 99.2 lbs. |
| Heaviest piece when disassembled: | 3W: 35 lbs. (front section) 4W: 44 lbs. (front section) |
| Standard seating: | Type: Foldable, compact, vinyl-covered molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17", Depth: 17" |
| Motor output: | 24-volt DC motor, sealed transaxle |
| Brakes: | Regenerative and electromechanical |
| Battery requirements ^{3,5} : | (2) 12V deep-cycle (standard) Size: (2) 18 AH, 14 lbs. each Weight: 29.5 lbs. per battery pack |
| Battery charger: | Off-board, 2 amp |
| Color: | 2 sets of exciting colors with every scooter! |



Red



Blue

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

FEATURES

- Feather-touch disassembly permits simple frame separation with only one hand
- Pride's exclusive black, non-scuffing tires
- Auto-connecting front-to-rear cable
- Includes 2 sets of easily changeable colored panels in Red and Blue
- Front frame-mounted seat post offers maximum stability
- All-new frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Standard front tiller-mounted basket included
- Deck basket for additional storage (4-Wheel only)
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board
- Charger port in tiller

Pride® Lifts & Ramps

Compatible Lifts:

- Backpacker® Plus • Outlander Full Platform
- Backpacker® AVP • Outlander TM
- Olympian



930 E. Main • Farmington, NM
(505) 327-4041



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®