

VICTORY[®] 10

LX WITH CTS SUSPENSION
4-WHEEL SCOOTER

A SMOOTH RIDE FOR YOUR ACTIVE LIFESTYLE

The **Victory[®] 10 LX with CTS Suspension** offers a smooth ride with performance to match. Comfort-Trac Suspension (CTS) is the next generation in mobility scooter ride comfort. Pride's industry first technology incorporates advanced suspension components for improved absorption over rough surfaces and a more comfortable ride experience over various terrains. Standard features include feather touch disassembly, wraparound delta tiller, 10" black non-scuffing tires, lightweight 8-position seat, LED lighting package (including curb and rear lights and directional signals) and a front basket. A 400 lb. weight capacity, a per charge range of up to 16.16 miles and a maximum speed of 5.6 mph provides versatility for both indoor and outdoor use. Available in True Blue and Candy Apple Red.



Shown in **True Blue**

CTS SUSPENSION



Front Suspension



Rear Suspension



facebook.com/PrideMobilityProductsCorp



youtube.com/PrideMobility



PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

SPECIFICATIONS

VICTORY® 10 LX WITH CTS SUSPENSION

4-wheel

Model # S710LX

Weight capacity:	400 lbs.
Maximum speed ¹ :	Up to 5.6 mph
Ground clearance ² :	2.2" at motor
Turning radius ² :	59.9"
Overall length ² :	47"
Overall width ² :	22.2"
Seat-to-floor height:	17.7"
Front tires ² :	3.5" x 10" solid
Rear tires ² :	3.5" x 10" solid
Suspension:	Front and rear
Range per charge ^{1,4} :	Up to 16.16 miles
Maximum allowable incline:	6°
Total weight without batteries ⁶ :	156.2 lbs.
Heaviest piece when disassembled:	77.6 lbs. (front section)
Standard seating:	Type: Folded moldable plastic Weight: 27.8 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drivetrain:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes:	Regenerative and electromechanical
Battery requirements ⁵ :	(2) 12-volt, deep cycle Size: 40 AH (standard) Weight ³ : (40 AH) 32.5 lbs. each
Battery charger:	5 amp, off-board charger
Color:	<div>   </div> <div> Candy Apple Red True Blue </div>

FEATURES

- Comfort-Trac front and rear suspension
- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Delta tiller with wraparound handles
- Backlit battery gauge
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination with a courtesy light under tiller
- Lightweight pinchless hinge seat eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Storage compartment below tiller
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port
- Auto-connecting front-to-rear harness

OPTIONS

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag
- Cell phone holder
- Touch-up paint

Pride® Lifts & Ramps

Compatible Lifts:

- Backpacker® Plus
- Outlander



930 E. Main • Farmington, NM
(505) 327-4041

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.